

Sliding Steel Door Single-Skinned ew-RP

optionally with wicket door



Text example

Compile and tender according to requirements.
Please refer to Technical Data below for respective details.
Updated 01.01.2011

Position	No. of pieces	Item	Unit price €	Total price €
		Sliding steel door "ew-RP1", single-skinned. Single-leaf door opening to the left. Door leaf made of tubular profiles RP 1087, 40 mm thick, on 4 sides. Door leaf filling made of 0.63 mm thick, ribbed steel plate Door leaf/seal galvanized and powder coated similar to RAL 9016 (traffic white). Door suspension consisting of tubular runner rail with double twin running gears. "Teckentrup ew-RP" or equivalent.		
		Ordering dimensions: Modular dimensions: _____ mm wide and _____ mm high Ordering details: Wall and header thickness (concrete _____ mm/masonry _____ mm) Door left/right opening (seen from the fixing side of the door). Headroom _____ mm (min. 155 mm or 185 mm for wall attachment) Left-hand space _____ mm (clear width +70 mm [slide-back area]) right-hand space _____ mm (min. 40 mm), with/without wicket door		



Technical data

Product: Sliding steel door ew-RP, single-skinned

Installation in: Walls made of:

- Masonry
- Concrete
- Autoclaved aerated concrete
- Steel construction

Dimensions: Modular dimensions
Width: 1000 – 4000 mm
Height: 2000 – 4500 mm

Opening direction: Opens to the right or left

Door leaf: Door leaf frame:
RP 1087 galvanized, on 4 sides
Door leaf thickness: 40 mm
Reinforcement: RP 152 galvanized (bars)
Running gear S3 or S4 depending on the door weight. Doors higher than 2500 mm are manufactured in two parts.
Door filling: Steel plate 0.63 mm thick, ribbed or with smooth or embossed sheet steel filling 1.5 mm, galvanized

Special equipment:
Two-leaf door up to modular width of 8000 mm
Door filling: Sheet steel smooth or embossed, corrugated grille

Door seal: Seal for rear bottom door edge

Surface: Door leaf and seal galvanized and powder coated, similar to RAL 9016 (grey white),

Fittings:

- Tubular runner rails with height-adjustable double twin running gears on ball bearings
- 2 rail stoppers
- 2 handles
- Mortice hook lock
- Profile cylinder 30.5 + 30.5 mm

Wicket door: Between two tubular profiles RP 1087 (with threshold)

- Door leaf frame: RP 152, galvanized, on 4 sides
- Door filling: Sheet steel 0.63 mm thick, ribbed, galvanized
- Door leaf thickness: 40 mm
- Fitting: 2 three-piece hinges
- Mortice lock with lever/knob in acc. with DIN18250, prepared for profile cylinder.
- Special black handle set

Special equipment:
Profile cylinder 30.5 + 30.5 mm
Panic lock

Special equipment:

- Rain guard

Sliding Steel Door Single-Skinned ew-RP

optionally with wicket door

