

Text example

Compile and tender according to requirements.
Please refer to technical data below for respective details.
Updated 1st June 2015

Position	No. of pieces	Item	Unit price €	Total price €
		Single-skinned garage door ew-1. Single-leaf element which can be used left/right handed. Out-side type of handing. Door leaf made of galvanized hollow profiles, 50 mm thick, 4-sided, with flange for holding the infill. Door leaf with vertically ribbed steel sheet panels and galvanized and powder coated corner frame, similar to RAL 9016 (Traffic white). Corner frame, 4-sided. Special lock with latch lever, prepared for profile cylinder. Black round handle set. 2 two-piece special hinges "ew-1" or comparable.		

Technical data

Product: garage door ew-1

Installation in:

- Masonry
- Concrete

Dimensions: modular dimension-width: 875 - 1250 mm
modular dimension-height: 1875 - 2375 mm

Handing: Single leaf garage side door. Door can be used DIN left or DIN right, inward and outward opening.

Door leaf: Leaf frame made of special hollow profiles 50 mm thick with flange for holding the infills. Two rear reinforcement elements.

Door leaf filled with vertically ribbed galvanized sheet steel, optionally horizontally ribbed sheet steel, cassette

Wooden filling - type of wood: vertically arranged Norway spruce, optionally horizontal or diagonal, door leaf frame without plinth

Special equipment – filling:
corrugated grille,
perforated sheet Ø10x14

Door leaf thickness: 50 mm

Frame: Corner frame 1.5 mm thick galvanized and powder coated similar to RAL 9016 (Traffic white), with seal. With three welded-on wall anchor plugs on each side.

Special equipment:
block frame

Surface: Door leaf frame/door leaf filling powder coated similar to RAL 9016 (Traffic white), Other RAL colours at an additional charge. Door leaf filled with panels with woodgrain design surface.

- Fittings:**
- Special hinges due to re-screwing of the hinges, optionally inward or outward opening.
 - Special lock prepared for profile cylinder with latch lever, can be used left/right, black round handle set (plastic)
- Special equipment:
- Profile cylinder (same closing as the up-and-over door type) 30.5 + 30.5 mm

Ordering dimensions (modular dimensions) width x height	Clear passage size width x height	
	with buffer	without buffer
875 x 1875	809 x 1805	809 x 1835
	1930	1960
1000 x 2000	934 x 1930	934 x 1960
	2055	2085
1000 x 2125	934 x 1930	934 x 1960
	2055	2085

Standard sizes:

Special sizes: up to 1250 x 2375 mm

