




EI₂30 „Teckentrup 62 FST“ Fire-resistant sliding steel door



Optionally with wicket door, optionally with glazing

Text example:

Fire-proof sliding steel door EI₂30 „Teckentrup 62 FST“ tested in accordance to EN 1634-1, for indoor use. Single-leaf door opening to the left. Galvanized door leaf, 62 mm thick (element design). With 3-sided door seal, galvanized. Door suspension consisting of tubular guide rail with double twin running gears. Automatic closing of the door due to counterweights in the protective box.

„Teckentrup 62 FST“ (classification with CE label according to EN 16034 / EN 13241) or equivalent.

(Compile and tender according to requirements. Please refer to technical data below for respective details. Updated 01.03.2020)

Technical data

	EI₂30 „Teckentrup 62 FST“ Fire protection closure for indoor use classification with CE label according to EN 16034 / EN 13241			
Approved wall types	Guide rail area:			
	▪ Concrete	min. 140 mm		
	▪ Masonry only side back area	min. 175 mm		
	▪ Covered steel beams	F60-A (EI 60)		
	Lateral walls:			
	▪ Concrete	min. 140 mm		
	▪ Masonry	min. 175 mm		
	▪ aerated concrete for reinforced autoclaved aerated concrete slabs	min. 200 mm		
	▪ covered steel beams	min. 175 mm		
		F60-A (EI 60)		
Approved dimensions	clear width:	500 - 8500 mm (8850 mm)		
	clear height:	1500 - 6000 mm (7125 mm)		
Installation	Lintel mounting or ceiling mounting, optional direct/ suspended ceiling mounting			
Opening direction	Door opens to the left or right			
Door leaf	Door leaf consisting of individual elements (number of elements acc. to opening width), double-skinned			
	Insulation:	mineral fibre and gypsum-boards		
	Sheet thickness:	1,0 mm		
	Element weight:	approx. 28 kg/m ²		
Door leaf thickness	62 mm			
Door seal	<ul style="list-style-type: none"> ▪ Galvanized seal profiles, 1,0 mm thick, on 3 sides (seal on 4-sides if smoke protection) ▪ Guiding shoe and guide rollers (lower door guide) ▪ Weight box with counterweights (behind the run-in side, radial damper mounting „rear“) Special equipment: Weight box slide-back area			
Surface	Door leaf (galvanized) and door seal Special equipment: Prime coat (similar to RAL 9002) RAL of choice version stainless steel			
Fittings	<ul style="list-style-type: none"> ▪ Tubular guide rails with height adjustable double twin running gears on ball bearings ▪ 1 Damping cylinders ▪ 1 Radial damper ▪ 1 recessed handle / 1 push handle ▪ 1 magnetic clamp ▪ 1 guiding rail cover 			
	Wicket door	Between two door leaf elements <ul style="list-style-type: none"> ▪ door leaf: double-skinned, rebated on 3-sides, without threshold. Opening to both sides possible. Clear dimensions of door (see pricing table): <ul style="list-style-type: none"> - Standard 1: 750 x 1800 mm - Standard 2: 1000 x 2010 mm - Standard 3: 1200 x 2100 mm (Special size e.g. for wheelchair users) ▪ Insulation: Mineral fibre and gypsum boards ▪ Sheet thickness: 1,0 mm ▪ Door leaf thickness: 62 mm ▪ Fitting: <ul style="list-style-type: none"> - 2 pieces of internal 3D hinges - Mortice lock with latch lever as per - Prepared for profile cylinder, special handle set, black - Slide rail door closer according to DIN EN 1154 ▪ Special equipment: <ul style="list-style-type: none"> - Profile cylinder 30,5 + 40,5 mm - Panic lock - Optionally two wicket doors 		
	Glazing	For door leaf and wicket door: <ul style="list-style-type: none"> ▪ Fire-resistant glass with steel glass holding strip 		
	Special equipment	<ul style="list-style-type: none"> ▪ Complete hold-open device consisting of: <ul style="list-style-type: none"> - ___ Piece smoke detectors, numbers of smoke detectors according to national specifications. - 1 magnetic clamp - 1 mains rectifier 220/24 V - 1 emergency release button - Acoustic alarm signal ▪ Complete electric drive (opener) ▪ Free-wheel function ▪ Mortice hook lock, Profile cylinder 35,5 + 40,5 mm ▪ Artificial buffer ▪ Artificial headroom (ceiling installation) 		
		# Different appearance of hot-dip galvanized surfaces! The surface of galvanized sheet can have different optics, which is no reason for rejection (e.g. dark or light grey parts, gloss or matt). DIN EN ISO 1461 is the standard for galvanizing.		

Further qualifications
(Special equipment)



Smoke proof in accordance to EN-1634-3 (available with wicket door)
Version door in stainless steel + smoke protection not possible



EI₂30 „Teckentrup 62 FST“ Fire-resistant sliding steel door

Further installation details see related installation instruction

